

## **GREENHOUSE**SUPPLEMENTAL - 3 BARS


360 Watts | RMH 61" | Lens Equipped
Same Spectrum • Less Energy Consumption
Energy Efficient & Even Light Distribution





**Customizable Recipes** 

Spectrum	Fixed Customized Recipes
Dimming	10-100%
Control	On-driver Knob / Megalight PC Software / Megalight External Controller / Customer External Input
Connectivity	Wireless LoRa/RJ12
PPFD	450 PPFD
Footprint @ RMH*	4ft * 4ft @ 61"

<sup>\*</sup>Recommended Mounting Height Above Canopy







Light Source	Osram & Seoul LEDs			
Lens angle	60 degree			
Lifespan	>50,000 hours			
Mounting	Universal Adjustable Hanging Included			
Dimensions & Weight	44.3" x 6.3" x 3.54"   15.7 lbs			
Ingress Rating	IP65			

340	390	420	430	430	430	420	390	340
360	410	440	450	450	450	440	410	360
400	435	450	450	455	450	450	435	400
410	425	440	450	450	450	440	425	410
400	420	440	445	450	445	440	420	400
410	425	440	450	450	450	440	425	410
400	435	450	450	455	450	450	435	400
360	410	440	450	450	450	440	410	360
340	390	420	430	430	430	420	390	340

7						
	Max Wattage (Line)	360w				
	Power supply	1 Unit of Upowertek BLD-400				
	Input Current	2.75 A @ 120Vac   1.38 A @ 240Vac   1.2 A @ 277Vac				
- T	Input Voltage	120/240/277Vac, 50/60Hz				
	Input Power Plug	Customizable				
	Power Factor	0.94 @ 240 Vac				

